



Nexgen
Fabrics

www.nexgenfabrics.com

Timberland



Light Beech

3011



Weathery Oak

3571



Exotic Wood

3572



Classy Dark

3382



Classy Cane

3383



Classic Teak

3931



Exotic Teak

3111



Farm Oak

3408



Honey Oak

3113



Exotic Oak

3413



White Oak

3251



Vintage Teak

3266

914.40 mm (36 inch)

Timberland Plank Size:












152.40 mm (6 inch)

NEXGEN FABRICS – The world class vinyl flooring is a quality product from Nexgen Fabrics pvt ltd. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring on state-of-the art plant & machinery equipped with latest technology and optimum quality control. Nexgen Fabrics has a wide sales distribution network across India.

TIMBERLAND is the latest collection of PVC wooden planks. The Shades and designs are carefully chosen to complement the natural wood. Manufactured with multi-layer technology, the premium flooring is highly suitable to handle heavy footfalls. The PUR protection layer ensures trouble free performance and enhance durability. It reduces the noise impact, is trendy, quick to install, easy to use and maintenance free. Finally, Timberland is termite and moisture resistant. Timberland planks are recommended for stores, malls, cafeteria, auditorium, hotels, schools, banks, homes, offices etc.

PERFORMANCE CHARACTERISTICS

| CHARACTERISTICS | SYMBOLS | TEST METHOD | RESULTS |
|-------------------------|---|---------------|--------------------------------|
| TYPE OF FLOORING |  | EN 649 | RESILIENT FLOORING |
| THICKNESS |  | EN 428 | 2.0 mm |
| SIZE |  | EN 427 | 152.4mm x 914.4mm (6" x 36") |
| SQAURENESS |  | EN 427 | ≤ 0.25 mm |
| WEAR LAYER | | | 0.2mm |
| DENSITY |  | EN 430 | 3500 g/m ² |
| DIMENSIONAL STABILITY |  | EN 434 | ≤ 0.25 mm |
| RESIDUAL INDENTATION |  | EN 433 | ≤ 0.10 mm |
| FLEXIBILITY |  | EN 435 | No Cracking using 20mm mandrel |
| COLOR FASTNESS |  | ISO 105 B02 | CLASS 6 |
| SURFACE SPREAD OF FLAME |  | BS 476 PART 7 | CLASS 1 |
| SLIP RESISTANCE |  | DIN 51130 | R9 |
| BEARING A CASTOR CHAIR |  | EN 425 | SUITABLE /CONTINUOUS USE |
| SURFACE PROTECTION |  | | PUR |

RECOMMENDATION FOR INSTALLATION

Timberland planks must be allowed to relax for 24 hours in room temperature between 18° C and 27° C prior to installation. Vinyl rolls are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation the base floor must be thoroughly clean, dry and free from grease & grit. We recommends use of fevicol SR 505 or any other equivalent rubber/acrylic based adhesive of similar type.

MAINTENANCE

Do's: After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution. Prevent point load indentation by covering your furniture legs with rubber stopper cabs. To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution. Scuff marks on the floor can be removed with little application of diesel. Use door coir or suitable mats to minimize accumulation of dust on Nexgen Fabrics vinyl flooring. Use water to remove any chemical spill on flooring.

Don'ts: Do not use any strong detergent, harsh cleaning agent or dry steel wool. Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor. Don't drag any heavy object or furniture on the flooring to avoid scratches on the floor.